

Registry

- 1 HKEY_CURRENT_USER
 - 1.1 HKEY_CURRENT_USER \ Software \ Stepover \ <AppName><MajorVersion>.<MinorVersion><CustomerName>
 - 1.2 HKEY_CURRENT_USER \ Software \ Stepover \ <AppName><MajorVersion>.<MinorVersion><CustomerName> \ Settings
 - 1.3 HKEY_CURRENT_USER \ Software \ Stepover \ <AppName><CustomerName>
- 2 HKEY_LOCAL_MACHINE
 - 2.1 HKEY_LOCAL_MACHINE \ Software \ StepOver \ <AppName><MajorVersion>.<MinorVersion><CustomerName>
 - 2.2 HKEY_LOCAL_MACHINE \ Software \ StepOver \ <AppName>

HKEY_CURRENT_USER

HKEY_CURRENT_USER \ Software \ Stepover \ <AppName><MajorVersion>.<MinorVersion><CustomerName>

Default installation:

- HKEY_CURRENT_USER \ Software \ Stepover \ eSignatureOffice 5.4

Customer installation:

- HKEY_CURRENT_USER \ Software \ Stepover \ eSignatureOffice 5.4 for XYZ

Key	Values	Description
Edition	Demo	Lizenzierte Edition
	Standart	
	WINTAB	
	TabletPC	
	WINTAB&Tablet	

HKEY_CURRENT_USER \ Software \ Stepover \ <AppName><MajorVersion>.<MinorVersion><CustomerName> \ Settings

Default installation:

- HKEY_CURRENT_USER \ Software \ Stepover \ eSignatureOffice 5.4 \ Settings

Customer installation:

- HKEY_CURRENT_USER \ Software \ Stepover \ eSignatureOffice 5.4 for XYZ \ Settings

Key	Values	Description
OnProgramIniError	<Encrypted String>	Encrypted Information how the application should behave when the program.ini is missing or damaged opieInformUser - inform User opieDontStart - don't start opieDoNothing - ignore Error

HKEY_CURRENT_USER \ Software \ Stepover \ <AppName><CustomerName>

Default installation:

- HKEY_CURRENT_USER \ Software \ Stepover \ PDF Converter

Customer installation:

- HKEY_CURRENT_USER \ Software \ Stepover \ PDF Converter for XYZ

Key	Values	Description
PDF parameters		Additional start parameters for the external application
FreePrinter	01h	obsolete
Language	D, E	Languages (D=German, E=English)
Language File	<Path>	Path to Languages file of the converter
Launch PDF processor	00h 01h	00h = will open the save under dialog after printing 01h = will start an external application after printing
PDF processor	<Path>	Path to the external Application which should be triggered after printing
INIDir	<Path>	Path to the configuration file of the PDF-Converter

HKEY_LOCAL_MACHINE

HKEY_LOCAL_MACHINE \ Software \ StepOver \ <AppName><MajorVersion>.<MinorVersion><CustomerName>

Default installation (32Bit System):

- HKEY_LOCAL_MACHINE \ Software \ StepOver \ eSignatureOffice 5.4

Default installation (64Bit System):

- HKEY_LOCAL_MACHINE \ Software \ **WOW6432Node** \ StepOver \ eSignatureOffice 5.4

Customer installation (32Bit System):

- HKEY_LOCAL_MACHINE \ Software \ StepOver \ eSignatureOffice 5.4 for XYZ

Customer installation (64Bit System):

- HKEY_LOCAL_MACHINE \ Software \ **WOW6432Node** \ StepOver \ eSignatureOffice 5.4 for XYZ

Key	Values	Description
InstallDir	<Path>	Installationpath
INIDir	<Path>	Path for the configuration file
HideSupportButton	"0" "1"	to disable the Support Form (with 0) of eSignatureOffice
Version	"5.4"	Installed Version
SSSDir	<Path>	Path for Signatur Set folder, in case the entry exist the values from the program.ini will be ignored
FTPDir	<Path>	Path for FTP Set folder, in case the entry exist the values from the program.ini will be ignored

HKEY_LOCAL_MACHINE \ Software \ StepOver \ <AppName>

It's possible to set up eSignatureOffice WebSign and SecureSign Modul to use a different configuration file ([Program.ini](#)) then the SOSigOffice.exe

32Bit System:

- HKEY_LOCAL_MACHINE \ Software \ StepOver \ WebSign
- HKEY_LOCAL_MACHINE \ Software \ StepOver \ SecureSign

64Bit System:

- HKEY_LOCAL_MACHINE \ SOFTWARE \ Wow6432Node \ StepOver \ WebSign
- HKEY_LOCAL_MACHINE \ SOFTWARE \ Wow6432Node \ StepOver \ SecureSign

Key	Values	Description
INIDir	<Path>	Path for configuration file (Program.ini)
SSSDir	<Path>	Path for Signatur Set folder, in case the entry exist the values from the program.ini will be ignored
FTPDDir	<Path>	Path for FTP Set folder, in case the entry exist the values from the program.ini will be ignored