

## naturaSign Pad Classic Technical Information

### naturaSign Pad Classic – Technical Information

#### Specific features:



At just one centimetre tall, the naturaSign Pad Classic is currently one of the thinnest LCD sign pads on the global market. Thanks to its flat construction, offset sensor surface and lower placement of the screen, and the “turn” button, with which the sign pad, and with it the surface for resting your hand, can be rotated through 180°, so for the first time left-handed as well as right-handed people can find the optimum position for writing: just like writing on a notebook.

The integrated LCD screen shows the signature in real time and can be used to view texts, graphics, parts of a document and

interactive buttons.

The naturaSign Pad Classic has a holder in the side for secure storage of the pen during transport, as well as another, vertical holder for when the pad is in use. The pen is held on a chord. For safe transportation on the move this pad is standardly delivered in the StepOver protective case.

#### The highest proof security on the market

Each naturaSign Pad Classic is provided with a unique certificate for the digital signing process (2048 bit RSA private key), with which the internal signature creation unit signs the document in a completely safe way. Furthermore, with this certificate the person examining the signed document can precisely assign the signature to a specific signature pad.

Apart from this, the processor of the signature pad contains a public key of a second key pair (RSA 2048 bit), generated by a notary public. By means of this key, the biometric data is already encrypted in the pad. This way, highly sensitive information can never be found in decrypted format in the unsafe “computer” environment (e.g. working space). The private key of this second key pair is safely deposited by the notary public.

The unique safety concept of this StepOver signature pad offers the user the highest possible proof security, since it is the only way they can provably claim they never used the biometric data of the signature for purposes other than intended (e.g. by intercepting and copying the data to another document).

The transfer of data is encrypted using a crypto-algorithm that is considered very secure (AES 256). With Windows 2000, XP, Vista, Win7, Win8 and Linux, it is not necessary to install a driver. The status lights and the screen show the status of the device (off: not connected; orange: ready; green: capturing signature).

The device has two holes in the back that enable it to be fixed to a desk or wall. Here you can download the relevant drilling template (mounting holes): <https://www.stepoverinfo.net/downloads/webseite/drilling-jig-Classic.pdf>

In cooperation with the international ecological organisation PrimaKlima Weltweit e.V., for each pad sold we plant an area of approximately 10m<sup>2</sup> with trees.





# natura Sign Pad Classic Technical Information

## Technical data:

Description	Referring to	Value	Measurement
Material	Casing	Polycarbonate	-
Width	Casing	15	cm.
Depth	Casing	12	cm.
Height	Casing	1	cm.
Width	Surface area of sensor and screen	10	cm.
Depth	Surface area of sensor and screen	2,9	cm.
Width	Active area of sensor	9,6	cm.
Depth	Active area of sensor	2,5	cm.
Length	Micro USB to USB cable	180	cm.
Weight	Sign pad without cable	150	grams
Temporal Definition emitted/real	Groups of 4D coordinates (Each group is made up of the coordinates X, Y, pressure and time)	500	Emissions per second
Temporal definition of the measurement	Internal Reporting rate (samples)	7000	Reporting rate 4D samples/sec (super sample 14 x (14 times greater))
Optical definition emitted/real	Definition of the captured X and Y coordinates (without adding some coordinates to other/without interpolation)	1000	DPI
Accuracy of repetition	Accuracy of repetition in X,Y measurements	+/- 0,1	mm
Screen definition	Definition of X and Y of the incorporated monochrome LCD. The screen on the pad shows the signature in real time and can be used to display texts and virtual surfaces.	320 x 85	pixels
Horizontal viewing angle	Left side / Right side	minimum 40° - typically 45°	°
Vertical viewing angle	Front / Opposite position	minimum 35° - typically 40°	°
Measurement of pressure	Maximum number of differentiated pressure levels	512	Levels of pressure
Minimum pressure	Lowest measurable writing pressure	1	Newton
Maximum pressure	Highest measurable writing pressure	10	Newton
Connection	Standard Micro-USB	Plug	-
Energy Use	No external power supply necessary	>100	mAh
Assistance for USB hibernation.	Not all computers or laptops deactivate the power in the USB ports when they hibernate. Because of this, only those external devices that transmit the computer's hibernation warnings and can turn themselves off actually help to save energy.	yes	Turns off screen, status lights, etc.
Type of transmission	HID encrypted with individual key and authorisation function. This device does not require a driver. It is recognised directly by Windows or Linux like a mouse or keyboard.	USB/HID	USB 2.0 ( USB 1.1 compatible)
Encryption Algorithm	Name of the standard cryptographic algorithm used for the transfer of data	RSA 2048 bit AES 256	-
Working temperature	Temperatures at which the pad will function according to what is specified here	0 to +50	°C with a max. of 90% RH without condensation.
Storage temperature	Temperatures at which the device can be transported and stored.	-10 to +80	°C with a max. of 90% RH without condensation.
Meets	Certificates	CE, WEE	-
Quality control measures for each device	Quality control and safety tests for all devices. The test protocols are linked to the serial number of the device and the name of the person who carried out the tests, and are available, free of charge, for our clients on request.	Testing of each device: Operation and margin for error in measurements	I/I





# natura Sign Pad Classic

## Technical Information

General quality control measures	Selection of component providers and documented production cycles.	StepOver GmbH only works with ISO certificated providers and works according to ISO regulations.	EN ISO 9000 ff
Identification / serial number	Each signature pad of this type has been given a unique serial number. The serial number can be found from the device's firmware and read on the display after insertion. There is also the option to add the serial number in figures for projects over 500 units and fix it as a barcode on the back of the device (subject to cost).	Bar code type (optional)	Code 39
Recycling	This product can be almost entirely recycled. The parts, such as the casing, etc. are marked with information about the materials used.	RAEE Registration Number	DE 27870259
Protecting the environment	The use of the sign pad saves paper. In cooperation with the international ecological organisation PrimaKlima Weltweit e.V. We also plant an area of approximately 10m <sup>2</sup> with trees for every sign pad of this type sold.	CO <sub>2</sub> neutral emissions	-
Country in which it is produced	Country in which the development, manufacture and quality control takes place.	Germany	Made in Germany
Accessories included	Standard Accessories.	Connection Cable, Instruction manual in multiple languages, Protective case	1x
Order number	GTIN article number	GTIN	4260130060848

### Important:

This product is protected by property rights and national and international patents.

We reserve the right to make technical changes that result in an improvement in the functioning of the device.

All names and trademarks are property of their respective owners.

The content and structure of this documentation are protected by copyright. The use of information, data, and especially of images, texts or sections of text without the express permission of StepOver is not permitted.

It is important that the indications given in the operating and security instructions are followed. The operating instructions can be found in the following electronic manual [www.StepOverInfo.net/MAN](http://www.StepOverInfo.net/MAN).

This product is not available for import, distribution or use in the USA. For products designated for the US market, contact StepOver Inc. ([www.US.StepOver.com](http://www.US.StepOver.com)).

Copyright StepOver GmbH 2013

